



19-01

TRANSFORMER/CARTROL DISTRIBUTION KIOSK

Model #CRT-5H



Model CRT-5H-8 shown

- EEMAC 3R enclosure
- Designed as a compact, energy saving, heavy duty, weatherproof, pad mount style combination transformer, CDP and cartrol logic assembly for parking lots - suggested is cartrol '3' dual thermostat for maximum energy savings
- Compact size allows for installation of step down transformer, one CDP and optional cartrol logic 1 to 5
- Energy saving feature allows parking lot to automatically cycle as related to outside air temperature
- 3 Point padlockable handle on CDP and safety bolt hinged door on transformer section - end accessible
- Open bottom pad mount style
- ASA 61 grey powder coat finish

Model #	kVA	PH	Primary Volts	Secondary Volts	CDP cct	CDP Amp	Dimensions (") H x W x D
CRT-5H-0	25	1	600	240	18	150	48 x 32 x 24
CRT-5H-1	37.5	1	600	240	30	250	48 x 32 x 24
CRT-5H-2	50	1	600	240	42	250	48 x 32 x 24
CRT-5H-3	75	1	600	240	42	400	72 x 45 x 36
CRT-5H-4	100	1	600	240	66	600	72 x 45 x 36
CRT-5H-5	167	1	600	240	66	1000	consult factory
CRT-5H-6	30	3	600	208	18	150	48 x 32 x 24
CRT-5H-7	45	3	600	208	42	250	48 x 32 x 24
CRT-5H-8	75	3	600	208	42	250	60 x 36 x 36
CRT-5H-9	112.5	3	600	208	66	400	72 x 45 x 36
CRT-5H-10	150	3	600	208	66	600	72 x 45 x 36
CRT-5H-11	225	3	600	208	72	800	consult factory

- available in various kVA & voltages - consult factory
- available in 460V primary - add suffix 460