

METERED TYPE POWER PEDESTAL - SPOONER SERIES

Model #5BE-DPP

- EEMAC 3R enclosure
- Specifically designed as a pad mount style, service entrance rated power pedestal for standalone exterior services as in RV's, mobile homes, park models, or park event power that require a utility metered connection point, meter socket, service entrance rated panel, and various outlets for cord connection, etc. with provision for various auxiliary loads such as outbuildings, hot tubs etc.
- Concrete base style complete with internal mounting bolts self venting design assembly
- Fitted with rear surface mounted 100A 120/240V kilowatt hour meter socket prewired to service entrance rated MCB
- Internal outlet box is mounted so cords are plugged in from side to allow safe and secure cable bend and either use of angle or direct end plugs
- Parks Green powder coat finish

Options

- Assembly without rear meter socket
- Meter socket complete with oversized #6-250MCM line lugs
- Internal water faucet • Water faucet heater

Model #	Dimensions (") H x W x D	Amps	Wire	Volts	Meter Bus	M.S. Line Lug	CDP Size
5BE-DPP-1	60 x 15.5 x 6	50	3	120/240	100A 4 JAW	6 - 1/0 MCM Cu/Al	12/24
5BE-DPP-2	60 x 15.5 x 6	79	3	120/240	100A 4 JAW	6 - 1/0 MCM Cu/Al	12/24
5BE-DPP-3	60 x 15.5 x 6	100	3	120/240	100A 4 JAW	6 - 1/0 MCM Cu/Al	12/24
5BE-DPP-4	consult factory	200	3	120/240	100A 4 JAW	6 - 250 MCM Cu/Al	12/24



21-01

Model
#5BE-DPP-3
Shown

Notes:

- Meter socket line lug is 6 - 250MCM Cu/Al
- Available in direct burial style (5B-D Series)