



21-01



Easy installation.  
No base required,  
ideal for remote  
locations

Model  
#5F-DPP-3  
shown

## DIRECT EARTH BURIAL SE PEDESTAL Model #5F-DPP

- EEMAC 3R enclosure
- Rainproof and sleet resistant for outdoor use
- Designed for locations where stand alone, service entrance metered distribution is required complete with meter socket and/or main breaker
- Service entrance rated 120/240V 10kAIC
- Galvanized steel complete with ASA 61 grey finish
- Direct burial style pedestal complete with bottom opening for entry and exit
- Meter base mounted in top section, main breaker below
- Main breaker cover is hinged up, padlockable and sealable
- Underground lower 24" high non-removable cover is galvanized and formed for underground cable saver protection flange
- Overhanging hood has safety soft, machine formed corners for maximum safety, durability and weather protection
- Galvanized stabilizer legs (2) are supplied loose for easy installation

### Options

- BC Hydro 3" PVC riser duct
- Unit without main circuit breaker (consult factory about 5F0 series)
- Unit without meter socket - add suffix '-NMS'

Model #	Dimensions (") H x W x D	Amps	Phase	Wire	Volts	S.N. Rating	SE Main Breaker	Meter Base	Line Lug Size
5F-DPP-1	96 x 12.25 x 4.75	50	1	3	120/240	50A	2P 50A	100A 4J	6 - 2/0
5F-DPP-2	96 x 12.25 x 4.75	60	1	3	120/240	60A	2P 60A	100A 4J	6 - 2/0
5F-DPP-3	96 x 12.25 x 4.75	100	1	3	120/240	100A	2P 100A	100A 4J	6 - 2/0
5F-DPP-4*	96 x 13.25 x 4.75	200	1	3	120/240	200A	2P 200A	200A 4J	2 - 250
5F-DPP-5*	96 x 13.25 x 4.75	200	3	4	120/208	200A	3P 200A	200A 7J	2 - 250

\* 200A units are special. Consult factory.