



21-01



Model #DPP-R-RT-1 shown

ROOF MATE ROOFTOP POWER PEDESTAL

Model #DPP-R-RT

- Specifically designed as a base mounted pedestal of maintenance free design complete with receptacle for specific maintenance of equipment located on rooftop locations (see CEC Rule #26-710d&e)
- 44" high x 7" wide x 6" deep pedestal body complete with 10" x 10" screw-on galvanized base plate. Tall body allows for various roof insulation thickness
- 10.5" High removable front lower skirt to allow for membrane wrap installation
- Base is designed for easy fastening with various sized bolts (3/4" hole) or self tapping type screws as used by roofers
- Safety soft machine formed corners on hood for ultimate safety & soft European appearance
- ASA 61 Grey powder coat finish over galvanized steel, tunnel style body for durable assembly
- Devices are vertically fitted complete with back box, Model #DR45-RV-1 Handy Hood, & weatherproof cover to meet CEC Rule #26-708 for receptacles exposed to the weather
- Lower cavity is designed to fit with roofer gum ring/box & accepts insulation & sealant to support roofing seal to membrane
- CSA certified pedestal & assembly

Notes

- Back box complete with 3/4" threaded hub & model #DR45-RV-1 Handy Hood supplied & installed by Dandy
- Device & weatherproof cover supplied & installed by others (or optionally by Dandy)
- 10.5" High standard skirt size is to accommodate most standard installations. Confirm acceptance depending on site conditions. Taller skirt option is available

Model #	Receptacles (supplied by others)	
	Qty.	Description
DPP-R-RT-1-44	1	20A GFCI Duplex Receptacle