



22-01



WEATHERPROOF MAIN DISTRIBUTION CENTER

Model #PDC-F

- EEMAC 3R enclosure
- Specifically designed as a service entrance rated pad mount weatherproof power distribution center complete with CT/PT section and distribution CDP
- Oversized driphood and two overlapping padlockable doors complete with 3 point padlockable stainless steel handle and 4” snow kick
- Acceptable for bottom entry - 3” mounting flange turned in all around
- Main fused section is SE rated complete with lockable doors and neutral/bonding facility
- CT section has rear CT/PT mounting pan and hinged padlockable/sealable cover
- Distribution section complete with Siemens bolt in CDP
- Parks green powder coat finish
- Safety soft, machine formed corners on doors and hood
- CSA certified assembly

Notes

- Consult factory for quantity of circuits (will vary depending on type of circuit breaker selected)
- Consult factory for availability of circuits
- Specify line & load lug sizes at time of order
- Consult local utility for CT space approval

Model #	Dimensions (") H x W x D	Phase	Wire	Amps	Volts	Circuits	CT Space (") H x W x D
PDC-F-1	57 x 58 x 14	1	3	250	120/240	30	30 x 34 x 12
PDC-F-2	57 x 58 x 14	1	3	400	120/240	30	30 x 34 x 12
PDC-F-3	57 x 58 x 14	1	3	600	120/240	30	30 x 34 x 12
PDC-F-3A	72 x 72 x 16	1	3	800	120/240	**	36 x 34 x 14
PDC-F-4	57 x 58 x 14	3	4	250	120/208	30	30 x 34 x 12
PDC-F-5	57 x 58 x 14	3	4	400	120/208	30	30 x 34 x 12
PDC-F-6	57 x 72 x 16	3	4	600	120/208	30	30 x 34 x 14
PDC-F-7	57 x 58 x 14	3	4	250	347/600	**	30 x 34 x 12
PDC-F-8	57 x 58 x 14	3	4	400	347/600	**	30 x 34 x 12
PDC-F-9	57 x 72 x 16	3	4	600	347/600	**	30 x 34 x 14
PDC-F-10	72 x 72 x 16	3	4	800	347/600	**	36 x 34 x 14