



22-01

# WEATHERPROOF WALL MOUNT PANEL BOARD

Model #DLCR

- EEMAC 3R enclosure
- Designed as a heavy duty, weatherproof, wall mount single panel enclosure/assembly with bolt in style breakers for service or branch circuit exterior use complete with optional device plates
- ASA 61 grey door, galvanized body
- Steel construction - code gauge
- Rear mounting dimples - full top driphood complete with safety soft machine formed corners
- Hinged outer gasketed door complete with clasp closers
- Siemens 'P1' panel included MLO - 10kAIC
- Tin plated aluminum bus material
- Full ground bar
- Fully assembled and CSA certified

**Options**

- Seam welded EEMAC 12  or 4
- Aluminum  or stainless  EEMAC 3R  or 4X
- Fully ASA Grey 61 assembly
- Various powder coat colours
- Skid-mounted
- Full cage and skid
- Copper bus material
- Branch breakers and filler plates available
- Main breaker  service entrance style
- 3 point padlockable handle
- 480V  600V  models Siemens
- Side mounted device plates - 9" deep assembly
- 22kA and higher interrupting capacity
- 400A  to 1200A  ratings
- rear quick entry/exit box
- Contactor assembly - see model #DLCR-C

**Notes**

- When model #DP-A or #DP-B device plates are added depth goes to 9" on assembly
- Depending on contactors selected, assembly depth may increase 9" to accommodate HOA and contactor (consult factory)



Model #	Siemens P1 Panel Interior						Dimensions (") H x W x D
	Circuits	Main Amps	Phase	Wire	Lug Size	Voltage	
DLCR-18125-1	18	125	1	3	(1) 350 - 6AWG	120/240	35 x 24 x 7
DLCR-30125-1	30	125	1	3	(1) 350 - 6AWG	120/240	41 x 24 x 7
DLCR-42125-1	42	125	1	3	(1) 350 - 6AWG	120/240	47 x 24 x 7
DLCR-18250-1	18	250	1	3	(1) 350 - 6AWG	120/240	35 x 24 x 7
DLCR-30250-1	30	250	1	3	(1) 350 - 6AWG	120/240	41 x 24 x 7
DLCR-42250-1	42	250	1	3	(1) 350 - 6AWG	120/240	47 x 24 x 7
DLCR-18125-3	18	125	3	4	(1) 350 - 6AWG	120/208	35 x 24 x 7
DLCR-30125-3	30	125	3	4	(1) 350 - 6AWG	120/208	41 x 24 x 7
DLCR-42125-3	42	125	3	4	(1) 350 - 6AWG	120/208	47 x 24 x 7
DLCR-60225-3	60	225	3	4	(1) 350 - 6AWG	120/208	50 x 24 x 7
DLCR-18250-3	18	250	3	4	(1) 350 - 6AWG	120/208	35 x 24 x 7
DLCR-30250-3	30	250	3	4	(1) 350 - 6AWG	120/208	41 x 24 x 7
DLCR-42250-3	42	250	3	4	(1) 350 - 6AWG	120/208	47 x 24 x 7

Available In 66cct & 72cct & 480V, 600V & 400A - consult factory for sizes & dual panel style